

2' x 2' CCT and Wattage Selectable LED Flat Panel

- 2' x 2' size – easily fits into standard T-bar grid ceilings or can be surface mounted
- CCT selectable – panel easily switches between 3500K, 4000K and 5000K
- Wattage selectable – panel easily switches between 20W, 25W and 30W
- DLC V5.1 Premium
- Precision micro-optics and prismatic lens create uniform, glare-free light evenly distributed over entire panel
- Lightweight and ultra-thin (1.5”) – ideal for both new construction and retrofit applications
- High quality construction – steel housing and white powder coated steel frame create the ultimate in durability
- 125 lm/W - cost-effective solution for high lumen output
- 0-10V dimming with a flicker-free driver – supports compliance with Title 24
- Suitable for damp locations
- 100-277V - accommodates Class 1 and Class 2 wiring circuitry
- 50,000 hour rated lifetime
- 5-year Limited Warranty



Specifications	
Model	BP22-3W-3CCT-P
Part Number	71163
Color Temperature	3500/4000/5000K
Lumen Output	2500 / 3125 / 3750lm
Wattage	20 / 25 / 30W
Power Factor	0.91
CRI	83
Efficacy	lm/W
Dimmable	0-10V
Voltage	100-277V
Operating Temperature	-20°C to 40°C
Base	NA
Weight	77.6 oz.
Dimensions	23.74 x 1.50 x 23.74 in
Rated Lifetime	50000 Hours
DLC Product Listing	BP22-3W-3CCT-P

Certifications:



2' x 2' CCT and Wattage Selectable LED Flat Panel

Additional Images:



Diagrams:

